

NEW
ITEMS

Redi-Weld™

200 PSI Grade R Twin Line Welding Hose - Coupled Assemblies

APPLICATIONS:

- General Welding Service
- Meets RMA IP-7-2011

Cover: Red and Green EPDM (ACETYLENE USE ONLY)

Reinforcement: Spiral Polyester yarns

Tube: EPDM

Oil Resistance: Limited (Acetylene only)

Branding: Redi-Weld™ <Size> Grade R Acetylene only - STD, Duty-KX- Max. WP. 200 PSIG - Meets ARPM-IP-7-2011 couple with one inch long ferrules made in U.S.A.

Packaging: Coiled coupled assemblies in 25 and 50 foot lengths



FEATURES AND ADVANTAGES:

- EPDM tube and cover coupled with brass welding couplings

Service Temperature Range:- 40° F (-40° C) to + 180° F (+ 82° C)

Nominal Specifications

Part Number	Color	ID (in.)	Working Pressure (PSI)	Coil Length (ft.)	Approx. Weight (lbs/pc)
REDI-WELD-03X25	Red / Grn	3/16	200	25	5.0
REDI-WELD-03X50	Red / Grn	3/16	200	50	8.8
REDI-WELD-04X25	Red / Grn	1/4	200	25	6.4
REDI-WELD-04X50	Red / Grn	1/4	200	50	12.1
REDI-WELD-05X25	Red / Grn	5/16	200	25	7.6
REDI-WELD-05X50	Red / Grn	5/16	200	50	14.0

Redi-Weld™ Bulk Hose on Reels **NEW**

Nominal Specifications

Part Number	Color	ID (in.)	Working Pressure (PSI)	Coil Length (ft.)	Approx. Weight (lbs/pc)
REDI-WELD-03X700	Red / Grn	3/16	200	700	105
REDI-WELD-04X700	Red / Grn	1/4	200	700	147

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

