

NEW SIZE

Amphibian™

AMPH-BK™ Series

Heavy Duty Polyurethane Lined Wet or Dry Material Handling Hose

Now in black!



MADE IN THE USA

Phthalate FREE

General Applications:

- Fly ash collection
- Hydro excavation
- Industrial vacuum equipment
- Material handling – heavy duty abrasive
- Milling machine scrap recovery
- Rock, gravel, sand and crushed concrete vacuuming
- Sewer truck boom hose
- Shot blast recovery
- Slurry handling

Construction: Black PVC cover with polyurethane liner and rigid PVC helix.

Service Temperature: -40°F (-40°C) to +150°F (+65°C)*

Also Available:

SOLARGUARD™
ADVANCED UV PROTECTION

AMPH-SLR™ Series
SOLARGUARD™ version with High UV Resistance ideal for warmer/sunnier climates

Get more info: koa.link/solarguard

Features and Advantages:

- **Thick Amphibian™ Abrasion Resistant Polyurethane Liner** – Designed for wet or dry applications where severe abrasion is a factor. Provides longer hose life and lower operating costs versus rubber or PVC hoses.
- **Static Dissipative Cover** – Specially formulated to help prevent the build-up of static electricity for added safety and to help keep material flowing smoothly.
- **“Cold-Flex” Materials** – Hose remains flexible in sub-zero temperatures.
- **Convolved Cover Design** – Provides increased hose flexibility.
- **Oil Resistant Polyurethane Liner** – Resists most animal and petroleum based oils.
- **Phthalate Free**

Nominal Specifications

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	68°F	104°F	68°F	104°F			
AMPH-BK400	4	101.6	4.76	120.9	35	18	Full	28	8	100	1.95
AMPH-BK500	5	127.0	5.75	146.0	36	18	28	25	15	100/20	2.42
AMPH-BK600	6	152.4	6.81	173.0	30	15	28	25	18	100/20	3.50
AMPH-BK800	8	203.2	9.18	233.2	30	15	28	25	22	50/21	5.91
AMPH-BK1000	10	254.0	11.60	294.6	22	10	24	18	26	20	9.90

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.
NOTE: For details of the following compliances, refer to footnotes listed on page 63.
 *Actual service temperature range is application dependent.

PHthalate FREE⁽¹⁰⁾, RoHS⁽¹¹⁾

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.